



No.	Name	Note	No.	Name	Note
1	Angle valve	1/4"Flare	17	Refrigerant service valve	1/4"Flare
2	Discharge flange	3"	18	Connector	1/4"Flare
3	Solenoid valve	50%(NC)	19	Liquid injection connector	5/8"Flare, option
4	Solenoid valve	75%(NC)	20	Suction flange	4"
5	Solenoid valve	35%(NC)	21	Cable box	Standard
6	Liquid(oil or refrigerant) injection connector	3/8"Flare, option	22	Service flange	
7	Capillary	3"	23	Oil drain valve	option
8	Check valve	Low side	24	Oil level switch	option
9	Oil sight glass	150W/300W	25	Discharge Temp. sensor	110°C
10	Oil heater	Connector, option	26	Safety Valve	option
11	Oil filter cartridge	5/8"Flare, option	27	Economizer port	7/8", solder
12	Oil pressure differential switch	option	28	Oil sight glass	High side
13	Oil cooler connector(out)	5/8"Flare, option	29	Oil temp. sensor	option
14	Stop pin	option	30	Over flow port	option
15	Oil cooler connector(in)	5/8"Flare, option	31	Solenoid valve	Stepses(NO), option
16	Angle valve	1/4"Flare			

*All stop valves are optional

Dimensional Outline Drawing & Component Description
for Steplless or Modulating—Type Capacity Control Application

Hanbell Model
Date and Rev.

RC2-580B
07/31/2008 A

Drawn By
B.Lai



Micro Control Systems, Inc.

5877 Enterprise Parkway

Fort Myers, Florida 33905

Tel. (239) 694-0089 Fax (239) 694-0031

E-mail: compressors@mcscontrols.com

Hanbell Precise
Machinery Co., Ltd.



HANBELL