

The MODEM Specifications & Description

Product Specifications

Data.....	V.90, V.34, V.32bis, V.32 V.22bis, V.22, V.23, V.21 Bell 103/212
Error Control.....	V.42, MNP2-4
Data Compression.....	V.42bis, MNP5
Indicators.....	9 LED status indicators:
	PWR Power On
	TD Transmit Data
	RD Receive Data
	OH Off Hook
	CD Carrier Detect
	TR Terminal Ready
	AA Auto Answer
	56K V.90 or V.92 mode
	V34 V.34 mode
Phone Interface.....	2 standard (RJ-11) telephone jacks for telephone and line connections
Dimensions.....	6"w, 1.22"h, 4.72"d
Supplied Accessories.....	AC Adapter MCS-M9-M25 cable RJ-11 phone cable Installation Guide



Part # **MODEM**

Product Description

The MODEM is part of the hardware for the MCS Support System. Located on-site, its purpose is to provide a means for remote communication with MCS micro controllers, either stand-alone or as part of a network.

By using MCS-Connect software you can dial out from your PC and into the MODEM which, once it answers, will connect you with a MCS micro controller. Once connected, you can interact with the micro controller in real time. The supplied MCS-M9-M25 cable connects the MODEM directly to a MCS-8.

The MODEM is pre-programmed at MCS for use with MCS-8 or MCS-6.

Options

-230	90 to 264vac input power @ 47 to 63Hz
-------------------	--