



| No. | Name                                | Note              | No. | Name                       | Note                      |
|-----|-------------------------------------|-------------------|-----|----------------------------|---------------------------|
| 1   | Angle valve                         | 1/4"Flare         | 16  | Angle valve                | 1/4"Flare                 |
| 2   | Discharge flange                    | 2 1/2"            | 17  | Refrigerant service valve  | 1/4"Flare                 |
| 3   | Solenoid valve                      | 50%(NC)           | 18  | Solenoid valve             | Shipped(NC or NO), option |
| 4   | Solenoid valve                      | 75%(NC)           | 19  | Liquid injection connector | 5/8"Flare, option         |
| 5   | Solenoid valve                      | 25%(NC)           | 20  | Suction flange             | 4"                        |
| 6   | Liquid or refrigerant service valve | 3/8"Flare, option | 21  | Cable box                  | Standard                  |
| 7   | Capillary                           | 2 1/2"            | 22  | Service flange             |                           |
| 8   | Check valve                         | Low side          | 23  | Oil drain valve            | option                    |
| 9   | Oil sight glass                     | 150W/300W         | 24  | Oil level switch           | option                    |
| 10  | Oil heater                          |                   | 25  | Discharge Temp. sensor     | 110°C                     |
| 11  | Oil filter cartridge                |                   | 26  | Safety Valve               | 1"NPf,option              |
| 12  | Oil pressure differential switch    | Connector, option | 27  | Economizer port            | 7/8", solder              |
| 13  | Oil connector(out)                  | 5/8"Flare, option | 28  | Oil sight glass            | High side                 |
| 14  | Stop pin                            | option            | 29  | Over flow port             | option                    |
| 15  | Oil connector(in)                   | 5/8"Flare, option |     |                            |                           |

\*All stop valves are optional

UNIT  
SI: mm Imperial: (in)

|      |            |                                       |       |                    |
|------|------------|---------------------------------------|-------|--------------------|
| △    | 2014.08.21 | Dimension correction                  | Model | RC2-470B           |
| △    | 2012.11.06 | Dimension correction                  | Name  | Compressor outline |
| △    | 2012.04.19 | Delete 1.Connector 2.Oil temp. sensor |       |                    |
| Item | Date       | Modification                          |       | HANBELL Ver. 06    |