

# MCS-667 **Description & Specifications**



## **Description**

The MCS-667 pressure transducer is one of the most economic and durable options on the market for dealing with high-pressure industrial applications.

In addition to being CE and UL approved, the MCS-667 is capable of surviving high vibration. It includes a cavity built out of solid 17-4 PH stainless steel 1/4" SAE Female Flare fitting & Schrader valve; 7/16-20 UNF pipe thread which creates a leak-proof, all metal sealed system that makes the MCS-667 ideal for use with rugged HVAC environments. The MCS-667 has an output voltage of 0.5 to 4.5vdc (ratio metric) and is also overvoltage-protected in both positive and reverse polarity, which adds an extra layer of safeguard against short-circuiting caused by unpredictable power surges.

### **Specifications**

Pressure Range	0 to 667 psi (Gauge)
Housing	17-4 ph Stainless Steel wetted
Environmental Protection	IP66*
Operating Temperature	-40°F to 257°F (-40°C to 125°C)
Accuracy	.± 1% -4°F to 185°F (-20°C to 85°C)
•	± 2.5% -40°F to -4°F (-40°C to -20°C)
	± 2.5% 185°F to 257°F (85°C to 125°C)
Agency Approvals	CE, UL 508
Proof Pressure	2 x Full Scale = 1334 psi
Burst Pressure	5 x Full Scale = 3335 psi
Random Vibration	20 G @ 10-6670 Hz
Input Voltage	5vdc
Output Voltage	
	1/4" SAE Female Flare fitting &
	Schrader valve; 7/16-20 UNF thread

Option Cable:						
Connector	Packard with Neoprene seal					
Length	20', 40' or 60' feet					
Type	3-conductor, 20 awg stranded					
Shield	Foil shield with 25% overlap					
Drain	Stranded tinned copper drain					
Part number description when ordering (MCS-667-xx)						



The cable is available in either 20', 40 or 60' lengths with a removable Packard connector to provide easy serviceability. The wire is sealed and crimped to the Packard connector providing a liquid tight environment and strain relief. Media compatibility: Refrigerants (freons) and ammonia.

\* IP66 Enclosure - IP rated as "dust tight" and protected against heavy seas or powerful jets of water.

#### **PSI to VDC**

. 0. 10 12 0													
PSI	SI (vdc)	PSI	SI (vdc)	PSI	SI (vdc)	PSI	SI (vdc)	PSI	SI (vdc)	PSI	SI (vdc)	PSI	SI (vdc)
0	0.50	100	1.10	200	1.70	300	2.30	400	2.90	500	3.50	600	4.10
10	0.56	110	1.16	210	1.76	310	2.36	410	2.96	510	3.56	610	4.16
20	0.62	120	1.22	220	1.82	320	2.42	420	3.02	520	3.62	620	4.22
30	0.68	130	1.28	230	1.88	330	2.48	430	3.08	530	3.68	630	4.28
40	0.74	140	1.34	240	1.94	340	2.54	440	3.14	540	3.74	640	4.34
50	0.80	150	1.40	250	2.00	350	2.60	450	3.20	550	3.80	650	4.40
60	0.86	160	1.46	260	2.06	360	2.66	460	3.26	560	3.86	660	4.46
70	0.92	170	1.52	270	2.12	370	2.72	470	3.32	570	3.92	667	4.50
80	0.98	180	1.58	280	2.18	380	2.78	480	3.38	580	3.98		
90	1.04	190	1.64	290	2.24	390	2.84	490	3.44	590	4.04		

Revision - 2016-08-15