



MCS-WIRELESS-MODEM-B

Description & Specifications



USA USE ONLY

Part # **MCS-WIRELESS-MODEM-B**

Description

The **MCS-WIRELESS-MODEM-B** is a compact industrial 4G (LTE) router equipped with 2 Ethernet ports, WiFi and RutOS software for advanced networking solutions. It delivers high performance for mission-critical cellular communication in rigorous environments, where wide operating temperature is required. Equipped with external SIM holder, digital input/output and signal strength status LEDs, it ensures easy network management. External SMA antenna connectors make it possible to attach desired antennas and easily find the best signal location.

The Wi-Fi is functional in both: Access point and Station mode at the same time.

- Supports 4G LTE data on AT&T, Bell, T-Mobile
- Creates a WiFi and Ethernet network to share the cellular connection with other devices (802.11 b/g/n)
- 4G (LTE-FDD): Band 4 and Band 13
- 1 x Digital input, 0 - 6 V detected as logic low, 8 - 30 V detected as logic high
- 1 x Digital open collector output, max output 30 V, 300 mA
- 2 x SMA for LTE, 1 x RP-SMA for WiFi antenna connectors

KIT INCLUDES

- MCS-WIRELESS-MODEM-B
- Din Rail mounting kit
- 9 W power supply
- 2 x LTE antennas (swivel, SMA male)
- 1 x WiFi antenna (swivel, RP-SMA male)
- 4G Mini Magnet-Mount Antenna
- 7ft CAT 5e Crossover Patch Cord, Orange
- USB-VPN Config File



(Standard Sim card NOT supplied)
SIM CARD MUST HAVE DATA AND SMS



An annual license and maintenance fee is charged for these units, consult MCS SALES for more information.

Physical Specifications

Casing material Aluminium housing
 Dimensions (W x H x D) 3.27" x 2.91" (83 x 25 x 74 mm)
 Weight 0.27lb (125 g)
 Mounting options Bottom and sideways DIN rail

MOBILE

Mobile module 4G (LTE) – Cat 4 up to 150 Mbps
 3G – Up to 42 Mbps
 2G Up to 236.8 kbps

FREQUENCY

North America 4G (LTE-FDD): B2, B4, B12
 3G: B2, B4, B5

WIRELESS

WiFi security WPA2-Enterprise - PEAP, WPA2-PSK, WEP, WPA-EAP, WPA-PSK; AES-CCMP, TKIP, SSID

Wireless Hotspot Captive portal (Hotspot)

ETHERNET

WAN 1 x WAN port (can be configured to LAN) 10/100 Mbps

LAN 1 x LAN port, 10/100 Mbps

CARRIERS

SIM CARD (not supplied) - MUST HAVE DATA AND SMS

Sim Card AT&T, T-Mobile and Bell

See current carrier list on: www.mcsccontrols.com

NETWORK

Routing Static routing, Dynamic routing
 Network protocols TCP, UDP, IPv4, IPv6
 Firewall Port forward, traffic rules, custom rules
 DHCP Static/dynamic IP allocation, DHCP Relay

SYSTEM CHARACTERISTICS

RAM 64 MB, DDR2
 FLASH storage 16 MB, SPI Flash

POWER

Connector 4 pin industrial DC power socket
 Input voltage range 9 – 30 VDC
 Power consumption < 6.5 W Max

OPERATING ENVIRONMENT

Operating temperature -40°F to 167°F (-40 C to 75 C)
 Operating humidity 10 % to 90 % non-condensing
 IP Rating IP30

REGULATORY & TYPE APPROVALS

Regulatory CE, FCC, EAC, RoHS

Packaging

Ship Weight 2.50 lb (approx)
 Box Dimensions 9" x 4" 3" (approx)



Click for latest information for setup and current phone carriers