




*MCS Total
Solutions for all your
Control Needs*

SMARTDT[®] Chiller Upgrade Package(s)



Package with Touchscreen



Package with Industrial Control Panel



Effective 07/20/2020 - Industrial Control Panels shipped after the effective date will have the UL LISTED label affixed to the control panel. Certification provides the inspection authority and your customer evidence that the control panel complies with nationally recognized safety standards. This brochure describes a standard upgrade package for the Turbocor series chillers. Each control upgrade installation is unique. It may be necessary to add additional options to the standard upgrade as described in this brochure. Fill out the brief questionnaire in the back of this brochure and forward to your sales representative for an estimate.



SMARTDT® Typical Upgrade

Package with Industrial Control Panel

Concerns:

- Old controls failed
- Wanted controls that were easier to understand and greater reliability, plus better and clear information

Equipment:


- Smardt and other brands Water Cooled Chillers
- One to Four Turbocor® Compressors
- One to Four Staging Valves
- Load balancing EXV control
- Modulating condenser water valve

Steps Taken:

- Remove existing controls
- Install MCS controls
- Reprogram boards for communication
- Provide on-site training and support for contractor to better understand MCS controls.

Results:

One Smardt® Chiller upgraded with MCS controls and one satisfied customer who is very happy with all the information and data available compared to the competitor's controls.



MCS MAGNUM with TOUCHSCREEN



Part # **MCS-MAGNUM-15.4-12**

Description

The **MCS-MAGNUM-15.4-12** consists of a MCS-MAGNUM controller along with a Touchscreen 15.4 in display.

The **MCS-TOUCH-15.4-12** is a new touchscreen interface designed to simplify user access with the **MCS-MAGNUM-N** utilizing **MCS-CONNECT** to provide both graphics and service mode access to technicians. Information and graphics on the TOUCH-15.4 are shown on a 15.4" high resolution (1280x800) LCD display with LED backlighting, which will guarantee long-life operation.

The **MCS-TOUCH-15.4-12** can connect up to 60 MCS controllers and supports RS485 or Ethernet networking.

The MCS-TOUCH-15.4-12 makes it easy for the user to manage more complex installation diagrams, without losing the overall view of the installation, as well as ensuring that the pages can be browsed in a fast and straight forward manner.

The MCS-MAGNUM-N is a durable microprocessor based controller designed for the hostile environments in the HVAC/R industry. It is designed to be the primary manager of the package it is controlling. The Magnum provides flexibility with setpoints and control options that can be selected prior to commissioning a system or when the unit is live and functioning. Displays, alarms and other interfaces are accomplished in a clear and simple language that informs the user as to the status of the controller.

The MCS-MAGNUM-N is a UL Recognized Component under UL File #169780 and also ROHS compliant.

Complementing the Magnum micro controller are a variety of MCS expansion boards.

MCS-Magnaum Controller

Dimensions.....	12.0"w, 8.0"h, 2.0"d
Mounting Holes	Mounts on a backplane utilizing 8 through-hole studs
Operating Temperature.....	-40°F to +158°F (-40°C to +70°C)
Operating Humidity.....	0-95% Non-Condensing
Storage Temperature.....	-40°F to +158°F (-40°C to +70°C)
Microprocessor.....	Zilog eZ80 Acclaim! @ 50mhz
Sensor Inputs (SI).....	12 inputs 0-5vdc (10-bit A/D)
Digital Inputs.....	4 inputs 0 or 5vdc only
Relay Outputs (RO).....	10 outputs 6.3amps @ 230vac
Analog Outputs (AO).....	4 outputs 0-10vdc
Printed Circuit Board	Six layer with separate power and ground planes
Input Power (Standard)	+12vdc power in board from 95-265vac switching power supply 77°F (25°C) ambient, 20VA max
MCS-I/O Comm Port.....	1 @ 38,400 baud
RS-485 Comm Port.....	1 @ 19,200 baud
Ethernet.....	10/100 Mbps Ethernet
Real Time Clock.....	Battery backup
Power Detection.....	Automatic power fail reset

MCS-Touch 15.4

Dimensions.....	17"L x 12.11"W x 2"H
LCD Screen.....	15.4" (16:10 Diagonal) 1280 x 800 Resolution 5-Wire resistive touch w/Stylus pen
Gasket.....	HT800 Cellular Silicone NEMA 4 IP66 rated
Surface Treatment.....	Glare/Anti-Reflection ≤1.5%
Operating Temperature.....	-20°C to +65°C Operating Temperature
Operating Humidity.....	0-95% Non-Condensing
Storage Temperature.....	-25°C to +70°C Storage Temperature
Motherboard-Rev 4.0.....	Freescale i.MX6 Dual Core 800mhz 2Gb of 512mhz DDR3 RAM memory 16Gb of eMMC Flash memory 10m/100m/1G Ethernet 1 Micro-SD Slots 2 USB Host 2.0 Real Time Clock (RTC) w/ Battery 3 RS485 communication ports

Parts Included

90W 12VDC Power Supply

Input Voltage: 88 VAC to 264 VAC
Output Voltage: 12 VDC @ 7.5Amps
Input Current: 3A / 115 AC - 1.6A / 230AC
Output Rated Current: 7.5A
Size: 2.76" x 3.54" x 2.14 (W*H*D) (70*90*54.5mm)
7ft CAT 5e Crossover Patch Cord, Orange



Packaging

Ship Weight.....	8.73 lb (approx)
Box Dimensions.....	16" x 12.5" x 8" (approx)

MCS Industrial Control Panel



Part #
MCS-MAGNUM-MLB-15.4-12

Description

The **MCS-MAGNUM-MLB-15.4-12 Industrial Control Panel** is made of powder coated aluminum for durability and longevity. A left hand swing door is mounted with three eight-inch hinges for strength. A key lock is provided for security on the door while still giving easy access of the display. This panel is intended for use in an environment protected from the weather.

The MCS-MAGNUM-MLB-15.4-12 consists of a **MCS-MAGNUM**, a Touchscreen 15.4" display and a MCS-SI-BASE expansion board. The **MCS-TOUCH-15.4** is a touchscreen interface designed to simplify user access with the MCS-MAGNUM utilizing **MCS-CONNECT** to provide both graphics and service mode access to technicians. Information and graphics on the MCS-TOUCH-15.4 are shown on a 15.4" high resolution (1280x800) LCD display with LED backlighting, which will guarantee long- life operation.

Panel includes the following; 20A, and a 5A Single-Pole Circuit Breaker, a 5 port 10/100 Ethernet Workgroup Switch Industrial rated, Red Alarm Indicator, Yellow Warning Indicator, Emergency Stop Switch and 3 Position Run/Stop Selector Switch. There is also a electrical outlet for laptop plug-in power at the panel and a Ground Bar for Sensor input shields.

Critical safety components manufactured by MCS and installed in this panel are UL Recognized Components under UL File #169780 and are also ROHS compliant.

Complementing the MCS-MAGNUM micro controller are a variety of MCS expansion boards that allow for system expansion to a maximum of 112 inputs and 80 outputs.

Options are available for all MCS-MAGNUM Industrial Control Panels with Keypads or Touch Screens. These options are factory installed by MCS at time of purchase. Visit our website for options available.

Specifications

Certification.....UL508A

NEMA Rating – Type 1 Control Panel - IP20 Rating
Enclosure is intended for indoor use primarily to provide a degree of protection against contact with the enclosed equipment and is not protected from liquids.

Industrial Control Panel

Dimensions..... 22"w x 28.50"h x 8"d
Mounting Holes..... Mounts with four pre drilled 15/32" holes

Temp. Range for Control Panel & Touch Screen

Operating Temperature..... -4°F to 158°F (-20°C to 70°C)
Operating Humidity..... 0-95% Non-Condensing
Storage Temperature..... -4°F to 158°F (-20°C to 70°C)

MCS-12V Power Supply

Input Voltage..... 88 VAC to 264 VAC
Output Voltage..... 12VDC @ 8.5Amps
Input Current..... 2.5A/115VAC 1.5A/230VAC

MCS-MAGNUM Controller

Microprocessor..... Zilog eZ80 Acclaim! @ 50mhz
Sensor Inputs (SI)..... 12 inputs 0-5vdc (10-bit A/D)
Digital Inputs..... 4 inputs 0 or 5vdc only
Relay Outputs (RO)..... 10 outputs 6.3amps @ 230vac
Analog Outputs (AO)..... 4 outputs 0-10vdc
Printed Circuit Board..... Six layer with separate power and ground planes
MCS-I/O Comm Port..... 1 @ 38,400 baud
RS-485 Comm Port..... 1 @ 19,200 baud
Ethernet..... 10/100 Mbps Ethernet
Real Time Clock..... Battery backup
Power Detection..... Automatic power fail reset

MCS-SI-BASE Expansion Board

Sensor Inputs (SI)..... 16 inputs 0-5vdc (10-bit A/D)
Analog Outputs (AO)..... 4 outputs 0-10vdc
MCS-I/O Comm Port..... 1 @ 38,400 baud

Touch Screen 15.4 - Specification

LCD Screen..... 15.4" Diagonal (Aspect Ratio 16:10)
Dimensions..... 17"L x 12.11"W x 3.228"H
1280 x 800 Resolution
5-Wire resistive touch w/Stylus pen
Gasket..... HT800 Cellular Silicone
NEMA 4 IP66 rated
Surface Treatment..... Glare/Anti-Reflection ≤1.5%
Operating Temperature..... -20°C to +65°C Operating Temperature
Operating Humidity..... 0-95% Non-Condensing
Storage Temperature..... -25°C to +70°C Storage Temperature
Motherboard-Rev 4.0..... Freescale i.MX6 Dual Core 800mhz
2Gb of 512mhz DDR3 RAM memory
16Gb of eMMC Flash memory
10m/100m/1G Ethernet
1 Micro-SD Slots
2 USB Host 2.0
Real Time Clock (RTC) w/ Battery
3 RS485 communication ports

MCS Industrial Control Panel

MCS-MAGNUM-N-12



The **MCS-MAGNUM-N-12** is a durable microprocessor based controller designed for the hostile environments in the HVAC/R industry. It is designed to be the primary manager of the package it is controlling.

The Magnum provides flexibility with set points and control options that can be selected prior to commissioning a system or when the unit is live and functioning. The TouchScreen and MCS-CONNECT provide a clear and simple language that informs the user as to the status of the controller.


Touchscreen

The **MCS-TOUCH-15.4** is a high resolution interface designed to simplify user access with the MCS-MAGNUM utilizing MCS-Connect to provide both graphics and service mode access to technicians. Information and graphics on the MCS-TOUCH-15.4 are shown on a 1280x800 LCD display with LED backlighting, which will guarantee long-life operation.


The MCS-TOUCH-15.4 comes pre-loaded with the MCS-CONNECT program that allows you to view the unit's status, history, warnings, alarms, setpoints, and more, all in a user-friendly graphic format.

Standard screens include:

- System Overview Screen
- Compressor Overview Screen
- Evaporator/Condenser Overview Screen
- Documents




SYSTEM OVERVIEW



COMPRESSOR OVERVIEW



EVAPORATOR CONDENSER OVERVIEW SCREEN



OPTIONAL 'GRAPHS OVERVIEW SCREEN IN REAL TIME'



OPTIONAL CUSTOM GRAPHICS 'GAUGE OVERVIEW SCREEN'

SMARTDT[®] Typical Upgrade

MCS-SI-BASE

The **MCS-SI-BASE** provides a flexible and cost effective way to allow sensor input and analog output expansion for the **MCS MAGNUM**. Each MCS-SI-BASE has a stand-alone microprocessor which communicates with the MCS MAGNUM over the MCS-I/O port at 38,400 baud. All data is check summed with auto error correction. Because communication is over a RS-485 long distance two-wire differential network transmission system, the MCS-SI-BASE may be located up to 5,000 feet away. MCS-SI-BASE board can be powered by a 12VDC regulated power supply and has a automatic power fail reset system.



MCS-SI-EXT mounted to
MCS-SI-BASE

MCS-SI-EXT

The **MCS-SI-EXT** provides a flexible and cost effective way to allow sensor input and analog output expansion for the **MCS MAGNUM**. Each MCS-SI-EXT can be paired with a MCS-SI-BASE to double the number of inputs and outputs. Each MCS-SI-EXT board is powered by the MCS-SI-BASE board once it is stacked on top.

MCS-RO-BASE

The **MCS-RO-BASE** provides a flexible and cost effective way to allow relay output expansion for the MCS-MAGNUM. Each MCS-RO-BASE has a stand-alone microprocessor which communicates with a Magnum/Micromag over the MCS-I/O port at 38,400 baud. All data is check summed with auto error correction. Because the communication is over a RS-485 long distance two-wire differential network transmission system, the MCS-RO-BASE may be located up to 5,000 feet away. The MCS-RO-BASE board is powered by a 12VDC regulated power supply.



MCS-RO-EXT mounted to
MCS-RO-BASE

MCS-RO-EXT

The **MCS-RO-EXT** provides a flexible and cost effective way to allow relay output expansion for the MCS MAGNUM. Each MCS-RO-EXT can be paired with a MCS-RO-BASE to double the number of outputs. MCS-RO-EXT board is powered by the MCS-RO-BASE board once it is stacked on top.

MCS-PRESSURE TRANSDUCERS

The **MCS Pressure Transducers** are one of the most economical and durable options on the market for dealing with high-pressure industrial applications.

In addition to being CE and UL approved, MCS transducers are capable of surviving high vibration. They include a cavity built out of solid 17-4 PH stainless steel 1/4" SAE Female Flare fitting & Schrader valve; 7/16-20 UNF pipe thread which creates a leak-proof, all metal sealed system that makes the transducers ideal for use with rugged HVAC environments.



SMARTD[®] Typical Upgrade

MCS-T-100 Temp Sensor



An extremely fast acting temperature sensor built for demanding environments. It is ideal for high moisture locations with continuous freeze and thaw cycles. The sensor is potted with a thermally conductive RTV Cure Silicon Adhesive to guarantee durability and response. Its high accuracy allows for interchangeability in the field. The large resistance range allows the use of over 1000' of cable with no noticeable effect. The MCS-T100 sensor has the ability to move from 32°F to 212°F in approximately 10 to 15 seconds.

MCS-Wells/Tubes

The MCS-WELL was designed to be used with the MCS-T100 temperature sensor, although it has other applications. It is used in the 30HXC series chillers in the chilled water and condenser water lines. It comes pre-filled with heat conductive compound to aid in temperature to the sensor.



The **MCS-TUBE** can be epoxied to a discharge or suction line on the 30HXC series chillers in order to obtain temperature readings without the use of a well. It was designed to be used with the MCS-T100 temperature sensor and comes pre-filled with heat conductive compound to aid in transferring temperature to the sensor.

MCS-EPOXY

- Pre measured resins and hardeners in one tube
- Easy to use - bonds, seals, plugs, molds and rebuilds
- No special tools needed
- Can even harden under water




- Pressure tested to 1300 psi
- Temperatures up to 500 degree F
- Color Gray
- Density 15.9 lb/gal (1.9 g/cc)
- Hardness (Shore D) 85
- Tensile Strength 6000 psi
- Compressive Strength 18.000 psi
- Modulus of Elasticity 6 x 105 psi
- Shear Strength 700 psi

SMARTDT[®] Typical Upgrade

MCS-VOLTAGE-3PH

The **MCS-VOLTAGE-3PH** measures AC voltage between 200-600 AC. It is designed to monitor the voltage of each phase of the main input power to the unit. The MCS-VOLTAGE-3PH sensor provides three separate DC voltage outputs that correspond to the AC voltage it is measuring.



MCS-PHASE

The **MCS-PHASE** is a programmable 3-phase line voltage monitor with 25-fault memory, high temperature LCD display, easy setup and clear diagnostic readout of system faults. The MCS-PHASE was specifically designed to protect motors and other 3-phase loads from premature failure and damage due to common voltage faults such as unbalance, over/under voltage, phase loss, reversal, incorrect sequencing and rapid short cycling.



MCS-USB-RS485

The **MCS-USB-RS485** is a USB to RS485 cable that provides a fast simple way to connect a **MCS-MAGNUM** to a Laptop or PC.

The MCS-USB-RS485 cable contains a small internal electronic circuit board, which converts USB to RS485 with LED indicators for transmit (TX=Red) and receive (RX=Green).



MCS-EXV-DRIVER

The **MCS-EXV-DRIVER** is used for the positioning and control of Sporlan, Alco, Carel, and Danfoss bipolar expansion valves using an analog input of 0-10 VDC (0 VDC = 0% valve opening, 10 VDC = 100% valve opening). The MCS-EXV-DRIVER also supports overdriving on full opened and full closed voltage signals. The display decimal notifies when overdriving by blinking.



SMART[®] Typical Upgrade

MCS-RS-485 EXTENDER

For those installations requiring an RS-485 port to be accessible without the necessity of opening the Control Cabinet door, MCS offers the part shown above.

The MCS-RS-485-EXTENDER mounting plate can mount on the outside of your enclosure and plugs into the RS-485 port on the back of the keypad.

A removable three-position terminal block is provided for easy wiring. to the keypad.



MCS-SEHI/SERI

The **MCS-SEHI/SERI** are Electronically Operated Step motor flow control valves, intended for the precise control of liquid refrigerant flow. Synchronized signals to the motor provide discrete angular movement, which translates into precise linear positioning of the valve piston. Valve pistons and ports are uniquely characterized, providing improved flow resolution and performance. The MCS-SEHI/SERI valves are easily interfaced with MCS microprocessor based controllers.



BMS GATEWAY

The **MCS-BMS-GATEWAY** is a microprocessor based communication device that provides translation from BACnet IP to LonTalk, BACnet MSTP, or Johnson Control N2. Information that can be transmitted includes the status of control points, alarm information, digital inputs, analog inputs or setpoints.

The MCS-BMS-GATEWAY protocol is field selectable by setting jumper on the device. Using **MCS-CONFIG** and the CONFIG file for the MCS-MAGNUM, you can automatically create the program that is required by the MCS-BMS-GATEWAY. Then using a web browser you can download the program into the unit.



SET THE MCS MAGNUM TO:
BACNET DEVICE ID: 18103

SET MCS-MAGNUM TO:
IP ADDRESS: 192.168.18.202
SUBNET MASK: 255.255.255.0
DEFAULT GATEWAY: 192.168.18.1

SMARTD[®] Typical Points List

Relay Outputs

#	Output Name	Type	Description
M-1	SPAREM-1	Standard	Relay output not used
M-2	SPAREM-2	Standard	Relay output not used
M-3	SPAREM-3	Standard	Relay output not used
M-4	SPAREM-4	Standard	Relay output not used
M-5	SPAREM-5	Standard	Relay output not used
M-6	Cmp1I-Lock	Standard	Comp 1 J2 TurboCor Interlock
M-7	Cmp2I-Lock	User Logic	Comp 2 J2 TurboCor Interlock
M-8	Cmp3I-Lock	User Logic	Comp 3 J2 TurboCor Interlock
M-9	Warning	Standard	Warning Light: unit is in a safety condition prior to a safety shutdown
M10	Alarm	Standard	Alarm Light: unit is in a safety shutdown

1-1	Comp 1	Step w\ EXV	Compressor 1 Run Enable
1-2	SPARE1-2	Standard	Relay output not used
1-3	SPARE1-3	Standard	Relay output not used
1-4	SPARE1-4	Standard	Relay output not used
1-5	SPARE1-5	Standard	Relay output not used
1-6	SPARE1-6	Standard	Relay output not used
1-7	SPARE1-7	Standard	Relay output not used
1-8	SPARE1-8	Standard	Relay output not used
1-9	SPARE1-9	Standard	Relay output not used
1-10	SPARE1-10	Standard	Relay output not used

2-1	Comp 2	Step w\ EXV	Compressor 2 Run Enable
2-2	SPARE2-2	Standard	Relay output not used
2-3	SPARE2-3	Standard	Relay output not used
2-4	SPARE2-4	Standard	Relay output not used
2-5	SPARE2-5	Standard	Relay output not used
2-6	SPARE2-6	Standard	Relay output not used
2-7	SPARE2-7	Standard	Relay output not used
2-8	SPARE2-8	Standard	Relay output not used
2-9	SPARE2-9	Standard	Relay output not used
2-10	SPARE2-10	Standard	Relay output not used

3-1	Comp 3	Step w\ EXV	Compressor 3 Run Enable
3-2	SPARE2-2	Standard	Relay output not used

SMARTD[®] Typical Points List

Relay Outputs

#	Output Name	Type	Description
3-3	SPARE2-3	Standard	Relay output not used
3-4	SPARE2-4	Standard	Relay output not used
3-5	SPARE2-5	Standard	Relay output not used
3-6	SPARE2-6	Standard	Relay output not used
3-7	SPARE2-7	Standard	Relay output not used
3-8	SPARE2-8	Standard	Relay output not used
3-9	SPARE2-9	Standard	Relay output not used
3-10	SPARE2-10	Standard	Relay output not used

4-1	Cmp1Alarm	Standard	Comp 1 In Alarm Output
4-2	Cmp2Alarm	Standard	Comp 2 In Alarm Output
4-3	Cmp3Alarm	Standard	Comp 3 In Alarm Output

Sensor Inputs

#	Output Name	Type	Description
M-1	ChilWtrIn	MCST100	Chilled Water In Temperature
M-2	ChilWtrOut	MCST100	Chilled Water Leaving Temperature
M-3	CndWtrIn	MCST100	Condenser water incoming temperature
M-4	CndWtrOut	MCST100	Condenser water leaving temperature
M-5	CndLevel	User Defined	Condenser Level Sensor
M-6	LoPsi SW 1	DIGITAL	Mechanical Low Psi Switch Comp 1
M-7	HiPsi SW 1	DIGITAL	Mechanical High Psi Switch Comp 1
M-8	LoPsi SW 2	DIGITAL	Mechanical Low Psi Switch Comp 2
M-9	HiPsi SW 2	DIGITAL	Mechanical High Psi Switch Comp 2
M10	LoPsi SW 3	DIGITAL	Mechanical Low Psi Switch Comp 3
M11	HiPsi SW 3	DIGITAL	Mechanical High Psi Switch Comp 3
M12	CndFlow	DIGITAL	Monitors the condenser flow
M13	ChwFlow	DIGITAL	Monitors the chilled water flow
M14	Phaseloss	DIGITAL	Phase loss: phase imbalance
M15	Run/Stop	DIGITAL	Run/Stop/Hand Switch
M16	Emg/Stop	DIGITAL	Emergency Stop Switch

SMARTD[®] Typical Points List

Sensor Inputs

#	Output Name	Type	Description
1-1	Cmp1 Fault	TurboCorFault	Compressor 1 Fault Message
1-2	Ctrl Mode1	ModbusHex	Compressor 1 Control Mode
1-3	IGV Open%	MODBUS	Inlet Guide Vane%-Compressor 1
1-4	SuctPsi 1	MODBUS	Suction Pressure - Compressor 1
1-5	DiscPsi 1	MODBUS	Discharge Pressure - Compressor 1
1-6	CavityTmp1	MODBUS	Cavity Temperature-Compressor 1
1-7	InvertTmp1	MODBUS	Inverter Temperature-Compressor 1
1-8	ChokSpeed1	MODBUS	Choke Speed-Compressor 1
1-9	SurgSpeed1	MODBUS	Surge Speed-Compressor 1
1-10	ActSpeed1	MODBUS	Actual Speed-Compressor 1
1-11	ComPSIRat1	MODBUS	Compressor 1 Pressure Ratio
1-12	Cmp1Amps	MODBUS	Compressor 1 Amperage
1-13	M IGV1STPS	MODBUS	Inlet Guide Vane Steps-Compressor 1
1-14	SPARE1-14	SPARE	Sensor input not used
1-15	SPARE1-15	SPARE	Sensor input not used
1-16	SPARE1-16	SPARE	Sensor input not used
2-1	Cmp2 Fault	TurboCorFault	Compressor 2 Fault Message
2-2	Ctrl Mode2	ModbusHex	Compressor 2 Control Mode
2-3	IGV Open%	MODBUS	Inlet Guide Vane%-Compressor 2
2-4	SuctPsi 2	MODBUS	Suction Pressure - Compressor 2
2-5	DiscPsi 2	MODBUS	Discharge Pressure - Compressor 2
2-6	CavityTmp2	MODBUS	Cavity Temperature-Compressor 2
2-7	InvertTmp2	MODBUS	Inverter Temperature-Compressor 2
2-8	ChokSpeed2	MODBUS	Choke Speed-Compressor 2
2-9	SurgSpeed2	MODBUS	Surge Speed-Compressor 2
2-10	ActSpeed2	MODBUS	Actual Speed-Compressor 2
2-11	ComPSIRat2	MODBUS	Compressor 2 Pressure Ratio
2-12	Cmp2Amps	MODBUS	Compressor 2 Amperage
2-13	M IGV2STPS	MODBUS	Inlet Guide Vane Steps-Compressor 2
2-14	SPARE2-14	SPARE	Sensor input not used
2-15	SPARE2-15	SPARE	Sensor input not used
2-16	SPARE2-16	SPARE	Sensor input not used

SMARTD[®] Typical Points List

Sensor Inputs

#	Output Name	Type	Description
3-1	Cmp3 Fault	TurboCorFault	Compressor 3 Fault Message
3-2	Ctrl Mode2	ModbusHex	Compressor 3 Control Mode
3-3	IGV Open%	MODBUS	Inlet Guide Vane%-Compressor 3
3-4	SuctPsi 2	MODBUS	Suction Pressure - Compressor 3
3-5	DiscPsi 2	MODBUS	Discharge Pressure - Compressor 3
3-6	CavityTmp2	MODBUS	Cavity Temperature-Compressor 3
3-7	InvertTmp2	MODBUS	Inverter Temperature-Compressor 3
3-8	ChokSpeed2	MODBUS	Choke Speed-Compressor 3
3-9	SurgSpeed2	MODBUS	Surge Speed-Compressor 3
3-10	ActSpeed2	MODBUS	Actual Speed-Compressor 3
3-11	ComPSIRat2	MODBUS	Compressor 3 Pressure Ratio
3-12	Cmp2Amps	MODBUS	Compressor 3 Amperage
3-13	M IGV2STPS	MODBUS	Inlet Guide Vane Steps-Compressor 3
3-14	SPARE2-14	SPARE	Sensor input not used
3-15	SPARE2-15	SPARE	Sensor input not used
3-16	SPARE2-16	SPARE	Sensor input not used

4-1	EvapPsi	MCS-200	Evaporator Pressure
4-2	DiscPsi 1	MCS-500	Discharge Pressure 1
4-3	DiscPsi 2	MCS-500	Discharge Pressure 2
4-4	DiscPsi 3	MCS-500	Discharge Pressure 3
4-5	LiqPsi	MCS-500	Liquid Pressure
4-6	SuctTmp 1	MCST100	Suction Temperature - Compressor 1
4-7	SuctTmp 2	MCST100	Suction Temperature - Compressor 2
4-8	SuctTmp 3	MCST100	Suction Temperature - Compressor 3
4-9	DiscTmp 1	MCST100	Discharge Temperature - Compressor 1
4-10	DiscTmp 2	MCST100	Discharge Temperature - Compressor 2
4-11	DiscTmp 3	MCST100	Discharge Temperature - Compressor 3
4-12	LiqTmp	MCST100	Liquid Temperature
4-13	Disable 1	DIGITAL	Turns Off Compressor 1
4-14	Disable 2	DIGITAL	Turns Off Compressor 2
4-15	Disable 3	DIGITAL	Turns Off Compressor 3
4-16	Ambient	MCST100	Outdoor Air Temperature

SMARTD[®] Typical Points List

Sensor Inputs

#	Output Name	Type	Description
5-1	Net R/S	BMS RUN	Building Management interface Run/Stop
5-2	NetReset	BMS CW RSET	Building Management interface target reset
5-3	NetDmdLmt	BMS Dmd FLA%	Building Management interface for Demand %

Analog Outputs

#	Output Name	Description
M-1	Exv%	Electronic Expansion Valve Control Signal
M-2	StgValve1%	Compressor 1 Staging Valve
M-3	StgValve2%	Compressor 2 Staging Valve
M-4	StgValve3%	Compressor 3 Staging Valve
1-1	Demand 1%	Compressor 1 Speed Demand
1-2	SPARE1-2	Analog input not used
1-3	SPARE1-3	Analog input not used
1-4	SPARE1-4	Analog input not used
2-1	Demand 2%	Compressor 2 Speed Demand
2-2	SPARE2-2	Analog input not used
2-3	SPARE2-3	Analog input not used
2-4	SPARE2-4	Analog input not used
3-1	Demand 3%	Compressor 2 Speed Demand
3-2	SPARE2-2	Analog input not used
3-3	SPARE2-3	Analog input not used
3-4	SPARE2-4	Analog input not used

SMARTD[®] Information

Use fillable form below that you can email to: sales@mcscontrols.com

Company: _____ Phone: _____

Name: _____ Title: _____ Email: _____

Mobile: _____ Jobsite: _____

Chiller Manufacturer	Chiller Model Number	Chiller Serial Number	Refrigerant Type

Will existing panel enclosure be used? Yes No, MCS will supply new Industrial Control Panel

- How many Circuits? _____ How many compressors per circuit? _____
- Compressor Model(s) Comp #1: _____ Comp #2: _____ Comp #3: _____ Comp #4: _____
- What is the compressor's Full Load Amps (FLA)? Comp #1: _____ Comp #2: _____ Comp #3: _____ Comp #4: _____
- Does / Will unit have a refrigerant Level Sensor Yes No
 If no, MCS will control on Suction Superheat.
 If yes, is the Level Sensor located on: Evaporator **Condenser**
Level Sensor Model: _____ **Signal Output?** _____
- What model EXVS will you be using for: refrigerant level/superheat control? _____ How many EXVS? _____
- Does / Will you be using a staging valve for each compressor? Yes No
 (comes off the discharge of compressor BEFORE the check valve and goes back to suction side of compressor. Each compressor will have its own valve)
 If yes, what model valves? Comp #1: _____ Comp #2: _____ Comp #3: _____ Comp #4: _____
- Does / Will you be using a (LBV) load balancing valve (aka hot gas valve) on the unit? Yes No
 (comes off the discharge of compressor AFTER the check valve)
 If yes, what model valve? _____
- Will MCS control the Condenser? Yes No
 Condenser type? _____
 If Water Cooled, Modulating Condenser Bypass Valve for pressure ratio control? Yes No
 If Air Cooled, Common Condenser? Yes No
 If yes, how many fans? _____ If no, how many fans per circuit? _____ VFD on first fan, per circuit? Yes No
- Will MCS control the Evaporator? Yes No If yes, 1 or 2 pumps? _____ VFD's? Yes No
- Will the unit be communicating to BMS? Yes No
 What Protocol will be used to BMS? _____

COMMENTS (is there any other information we should know?):



5580 Enterprise Pkwy., Fort Myers, FL 33905

Office: 239-694-0089 • Fax: 239-694-0031

www.mcscontrols.com