



RELEASE NOTES

MCS-CONFIG Version 9.03Y 09/14/2012

Updates from previous versions:

New Features:

1. In MicroMag config types adding 2 new SI names = HW LV TEMP and HW LV HUMD and adding 4 new Set point names = #103-MORNING TEMP, #104-MORNING TIME, #105-HW DEFROST, #106-REHEAT FLUSH.
2. In MicroMag config types on the MicroMag info screen under the heating section on the first panel on the left adding a Morning Warm Up RO that will always be visible.
3. In MicroMag config types on the Setpoint info screen in the Set point Type column when the user selects the Time type the Time and Max Time Allowed columns are the only ones being used to set the time for the set point. Adding 6 new columns at the end of the set point grid that will be labeled Time A, Max Time A, Time B, Max Time B, and Time C, Max Time C. Also making the Time and Max Time Allowed columns null when the set point type is set to Time.

Bug Fixes:

1. In ACU config types on the SI Info screen in the Display Type column when the user selects MODE SEL SW as the display type they are allowed to enter a 1, 2, or 3 in the manual value column which selects the mode type. Changing this to only allow a 0, 1, or 2 with 0 being the default.
2. In MicroMag config types on the Set point info screen in the Set point Type column changing the Adjust set point type to a Delay set point type and all code that corresponds to the change. Making the new addition to the print function as well.

Any questions regarding this release, contact:
support@mcscontrols.com

Micro Control Systems, Inc. 5580 Enterprise Parkway Fort Myers, Florida 33905
(239)694-0089 FAX: (239)694-0031 www.mcscontrols.com

Information contained in this document has been prepared by Micro Control Systems, Inc. and is copyright © protected 2012. Copying or distributing this document is prohibited unless expressly approved by MCS.