



SOFTWARE RELEASE NOTES

MCS-CONNECT
Version 8.10M
05/04/2011

Updates from previous versions:

New Features:

1. Created new Status grids for REF V11 configurations.

Capacity Control State	Time	Wanted/ Actual	Step Delay	Def. Approach /Def. Time	Rate of Change	Control On	Wanted %	
UNIT IS OFF	00:00:31	0/0	29	20.0F / 00:03:00	54.0	VOLTAGE	N/A	
State	Time	PSI Diff	Sat. Evap.	Evap. Approach /Time	Evap. Superheat	FLA %	Forced Defrost	Lead?
1-1)CMP OFF/READY	00:01:30	61.0P	21.2	8.8F / 00:05:00	8.8	100	00:20:00	Yes
2-2)CMP OFF/READY	00:01:30	61.0P	21.2	8.8F / 00:05:00	8.8	100	00:20:00	
3-3)CMP OFF/READY	00:01:30	61.0P	21.2	8.8F / 00:05:00	8.8	100	00:20:00	
Suction Temp	Saturated Suction	Suction Superheat	Disc Temp	Saturated Discharge	Disc Superheat	RefType	Defrost Min	
1) 40.0	18.1	21.9	150.0	99.7	50.3	R404A	00:06:00	
2) 40.0	18.1	21.9	150.0	99.7	50.3	R404A	00:06:00	
3) 40.0	18.1	21.9	150.0	99.7	50.3	R404A	00:06:00	
Valve State	Time	Valve %	SuperHeat	SuperHeat ROC	ADJ Delay			
1-1) LLS IS CLOSED	00:00:01							
2-2) LLS IS CLOSED	00:00:01							
3-3) LLS IS CLOSED	00:00:01							

Bug Fixes:

- Fixed bug in software that was checking in an incorrect place to read the I/O board type.

Any questions regarding this release, contact:
support@mcscontrols.com

Micro Control Systems, Inc. 5580 Enterprise Parkway Fort Myers, Florida 33905
(239)694-0089 FAX: (239)694-0031 www.mcscontrols.com

Information contained in this document has been prepared by Micro Control Systems, Inc. and is copyright © protected 2012. Copying or distributing this document is prohibited unless expressly approved by MCS.