



MCS-MAGNUM-SB-10.1-12 INDUSTRIAL CONTROL PANELS



Part # **MCS-MAGNUM-SB-10.12**

Description

The **MCS-MAGNUM-SB-10.1-12 Industrial Control Panel** is made of powder coated aluminum for durability and longevity. A left hand swing door is mounted with two four-inch hinges for strength. A key lock is provided for security on the door while still giving easy access to the display. This panel is intended for use in an environment protected from the weather.

Critical safety components manufactured by MCS and installed in this panel are UL Recognized Components under UL File #169780 and are also ROHS compliant.

The MCS-MAGNUM-SB-10.1-12 consists of a **MCS-MAGNUM** along with a Touchscreen 10.1" display, a 20A Single-Pole Circuit Breaker. A 5 port 10/100 Ethernet Workgroup Switch Industrial rated. There is also a electrical outlet for laptop plug-in power at the panel and a Ground Bar for Sensor input shields.

Power is supplied using a MCS-12V power supply.

The **MCS-TOUCH-10.1** is a touchscreen interface designed to simplify user access with the MCS-MAGNUM utilizing MCS-CONNECT to provide both graphics and service mode access to technicians. Information and graphics on the TOUCH-10.1 are shown on a 10.1" high resolution (1280x800) LCD display with LED backlighting, which will guarantee long-life operation.

For information on the MCS-MAGNUM, see specifications on our web site. Complementing the MCS-MAGNUM micro controller are a variety of MCS expansion boards that allow for system expansion to a maximum of 112 inputs and 80 outputs. Communication to these units occur at 38,400 baud over the MCS-I/O port which is dedicated for this purpose.

Specifications

Certification..... UL508A

NEMA Rating – Type 1 Control Panel - IP20 Rating

Panel is intended for indoor use primarily to provide a degree of protection against contact with the enclosed equipment and is not protected from liquids.

Industrial Control Panel

Rated Voltage (Standard)..... 120VAC or 230VAC

Phase / Frequency..... 1 Phase / 60Hz

Full Load Current(approx)40A at 120VAC or 20A at 240VAC

Short Circuit Current Rating . 10kA

Dimensions..... 18.25"w x 19.5"h x 8"d

Mounting Holes..... Mounts with four pre-drilled 9/32" holes

Temp. Range for Control Panel & Touch Screen

Operating Temperature..... -4°F to 158°F (-20°C to 70°C)

Operating Humidity..... 0-95% Non-Condensing

Storage Temperature..... -4°F to 158°F (-20°C to 70°C)

MCS-MAGNUM Controller

Microprocessor..... Zilog eZ80 Acclaim! @ 50mhz

Sensor Inputs (SI)..... 12 inputs 0-5vdc (10-bit A/D)

Digital Inputs..... 4 inputs 0 or 5vdc only

Relay Outputs (RO)..... 10 outputs 6.3amps @ 230vac

Analog Outputs (AO) 4 outputs 0-10vdc

Printed Circuit Board Six layer with separate power and ground planes

Input Power (Standard) 12 vdc Regulated Power Supply

Minimum (Brown in) 9.44 vdc

Amp Draw (Loaded) 857.0 mA

MCS-I/O Comm Port 1 @ 38,400 baud

RS-485 Comm Port 1 @ 19,200 baud

Ethernet..... 10/100 Mbps Ethernet

Real Time Clock Battery backup

Power Detection Automatic power fail reset

MCS-Touch 10.1 Touchscreen

LCD Screen..... 10.1" Diagonal (Aspect Ratio 16:10)
1280 x 800 Resolution

5-Wire resistive touch w/Stylus pen

Gasket..... HT800 Cellular Silicone

NEMA 4 IP66 rated

Surface Treatment..... Glare/Anti-Reflection ≤1.5%

Operating Temperature..... -20°C to +65°C Operating Temperature

Operating Humidity..... 0-95% Non-Condensing

Storage Temperature -25°C to +70°C Storage Temperature

Motherboard-Rev 4.0 Freescale i.MX6 Dual Core 800mhz

2Gb of 512mhz DDR3 RAM memory

16Gb of eMMC Flash memory

10m/100m/1G Ethernet

1 Micro-SD Slots

2 USB Host 2.0

Real Time Clock (RTC) w/ Battery

3 RS485 communication ports

Packaging

Weight 40 lbs(approx)

Box 24" X 30" x 10"

5580 Enterprise Pkwy., Fort Myers, FL 33905

Office: 239-694-0089 • Fax: 239-694-0031 www.mcscontrols.com