



# MCS-POWERMETER-B

## Description & Specifications

cUL US  
LISTED  
Open-type Measuring  
and Testing Equipment  
E469787



Part # MCS-POWERMETER-B

### Description

#### A universal, digital 3 phase power meter

The **MCS-POWERMETER-B** is expertly designed for engineers who require a highly effective means of monitoring and displaying data. This panel-mounted 3-phase power meter is specifically tailored for mains circuits, potential transformers, and current transformers. With its multi-measurement capability for active and reactive power, it stands as the ideal choice for a diverse range of power monitoring applications, solidifying its position as the most flexible panel power meter for electrical monitoring.

Benefits include:

- Works with potential and current transformers
- Modbus® RTU over RS485 - communication as standard.
- 10 alarm set points
- Measures Active (W), Reactive (VAr) and Apparent (VA) power.
- Displays electrical parameters on large, backlit LCD display.
- Provides clear indication of electrical circuit performance.

### Specifications

Mounting Type .....	Panel Mount
Overall Dimensions .....	2.83" x 2.83" x 2.90" 72mm x 72mm x 74mm
Panel Cutout Dim. Square.....	2.68" x 2.68" 68.00mm x 68.00mm
Measuring Type Current .....	(3-Phase), Voltage
Voltage measurement range .....	L-L 10- 600VAC L-N 10 - 300VAC
Current measurement range .....	0 - 5A
Display Type Background.....	White
Analog Output.....	1 @ 4-20mA
Voltage - Supply .....	100 ~ 277VAC
Max power .....	2W
Supply Frequency.....	50-60Hz
Voltage OP Outputs .....	12-24AC/DC
Max sink current .....	15mA
Communication .....	Modbus® RTU over RS485
Termination Style.....	Screw Terminal
Operating Temperature.....	14°F ~ 122°F (-10°C ~ 50°C)
Weight .....	0.441 lb (200.03 g)
IP Rating.....	IP65, NEMA type 4 and 12
Certification.....	CE, RoHS, UL, cUL, UKCA

### Components

#### • MCS-POWERMETER-B-N

#### • MCS-POWERMETER-B-CT1000

Three(3) current transformers



Mounting Pass-through conductor  
Connection Type - Screw Terminal

Secondary Conductors -22-14 AWG copper only

Temperature range -20° to +50°C [-4° to +122°F]

Agency Approvals - RoHS, UL, CE

#### • Three-1AMP Fuses & 3 Pole Fuse Block



#### • One- 0.5AMP/250V & DINnector terminal block

### Packaging

Weight..... lbs (approx)  
Box..... (approx)